

MAINTAINING YOUR FLEXITEEK 2G DECK

CONGRATULATIONS ON PURCHASING THE NEXT GENERATION OF DECKING SYSTEM

Your Flexiteek deck does not require any special treatment or costly maintenance and by following these simple instructions your deck will last many years and continue to look great.

WASH

We recommend that you wash your deck with a medium stiff brush and Flexiteek Wash & Care soap.

STAIN/SPILL REMOVAL

Flexiteek is stain resistant and most spills will clean up with warm soapy water (for rapid stain removal, clean while stain is fresh). We recommend the use of a Flexiteek Cleaner; simply spray the Cleaner on the area, scrub with a white 3M doodle bug scrubber and rinse with water. Heavy stains should be removed using Flexiteek Deep Cleaner used with a red/green 3M doodle bug scrubber or a stiff scrubbing brush, rinse with water. If a slight mark remains after a spill, sand with 60grit sandpaper; remember to follow the grain. This will remove any remaining marks and the sanded area could have a lighter shade that will even out over time.

The above mentioned Flexiteek wash and cleaning products, can be ordered through: order@flexiteek.com

Over time, your Flexiteek deck may go darker and or lose some of its "graining". Should you wish to bring the look back to the original then; once again, sanding with 60grit sandpaper with a sanding block as described above will restore the color and texture. Unlike real teak, there is minimal material removed when sanding as described and there is no concern about sanding through if the above directions are followed.

Flexiteek may be power washed – power up till 135 Bar. This is the best way to clean out particles and dirt.

DO NOT use an orbital or belt sander on your Flexiteek deck.

DO NOT subject your Flexiteek deck to excessive heat, Chemicals, deck brightening chemicals, acid washes or any 2-part cleaners. Treat your Flexiteek deck with the care that you would a normal teak deck. Some modern cleaners may damage the soft caulking around the edge of a Flexiteek deck.

Flexiteek is designed to be left raw. DO NOT coat your Flexiteek deck with teak oil or oil based varnish. Flexiteek is synthetic and will not absorb fluids. For interior use you may sand your deck with 120-180grit sandpaper and coat with a good quality 2-part water based polyurethane floor finish. This has excellent adhesion and will give a nice polished surface. Beware that the floor may become slippery. This finish is not to be used for the exterior.

If you have any questions regarding the maintenance of your Flexiteek deck or would like to order Flexiteek Cleaner, please feel free to contact us on our support email: order@flexiteek.com

E&OE